

LMR®-195-UF **UltraFlex Communications Coax**

Ideal for...

- Jumper Assemblies in Wireless Communications Systems
- Short Antenna Feeder runs
- Any application that requires periodic/repeated flexing



• **LMR®- UltraFlex** has a stranded center conductor and rubber outer jacket designed for multiple bending/flexing cycles. It is used for both indoor and outdoor applications.

• **Flexibility** and bendability are hallmarks of the LMR-195-UF cable design. The flexible outer conductor enables the tightest bend radius available for any cable of similar size and performance.

• **Low Loss** is another hallmark feature of LMR. Size for size LMR has the lowest loss of any flexible cable and comparable loss to semirigid hard-line cables.

• **RF Shielding** is 50 dB greater than typical single shielded coax (40 dB). The multi-plated foil outer conductor is rated conservatively at >90 dB (i.e. >180 dB between two adjacent cables).

• **Weatherability:** LMR-195-UF cables are designed for outdoor exposure and have a life expectancy in excess of 10 years.

• **Connectors:** A wide variety of connectors are available for LMR cable including all common interface types, reverse polarity, and solder-on center pins. Most LMR connectors employ crimp outer attachment using standard hex crimp sizes.

• **Cable Assemblies:** All LMR-195-UF cable types are available as pre-terminated cable assemblies. Refer to the section on FlexTech for further details.

Construction Specifications				
Description	Material	In.	(mm)	
Inner Conductor	Stranded BC	0.038	(0.97)	
Dielectric	Foam Polyethylene	0.110	(2.79)	
Outer Conductor	Aluminum Tape	0.116	(2.95)	
Overall Braid	Tinned Copper	0.139	(3.53)	
Jacket	Black Thermoplastic Elastomer	0.195	(4.95)	


Mechanical Specifications				
Performance Property	Units	US	(metric)	
Bend Radius: installation	in. (mm)	0.5	(12.7)	
Bend Radius: repeated	in. (mm)	2	(50.8)	
Bending Moment	ft-lb (N-m)	0.01	(0.14)	
Weight	lb/ft (kg/m)	0.021	(0.03)	
Tensile Strength	lb (kg)	40	(18.2)	
Flat Plate Crush	lb/in. (kg/mm)	10	(0.18)	

Environmental Specifications			
Performance Property	°F	°C	
Installation Temperature Range	-40/+185	-40/+85	
Storage Temperature Range	-54/+185	-70/+85	
Operating Temperature Range	-40/+185	-40/+85	

Electrical Specifications			
Performance Property	Units	US	(metric)
Cutoff Frequency	GHz		41
Velocity of Propagation	%		80
Dielectric Constant	NA		1.56
Time Delay	nS/ft (nS/m)	1.27	(4.17)
Impedance	ohms		50
Capacitance	pF/ft (pF/m)	16.9	(55.4)
Inductance	uH/ft (uH/m)	0.095	(0.31)
Shielding Effectiveness	dB		>90
DC Resistance			
Inner Conductor	ohms/1000ft (/km)	9.5	(31.2)
Outer Conductor	ohms/1000ft (/km)	4.9	(16.1)
Voltage Withstand	Volts DC		1000
Jacket Spark	Volts RMS		3000
Peak Power	kW		2.5

Part Description				
Part No.	Application	Jacket	Color	Stock Code
LMR-195-UF	Indoor/Outdoor	TPE	Black	54212

Attenuation vs. Frequency (typical)



Frequency (MHz)	30	50	150	220	450	900	1500	1800	2000	2500	5800
Attenuation dB/100 ft	2.3	3.0	5.3	6.4	9.3	13.2	17.7	19.0	20.1	22.6	35.6
Attenuation dB/100 m	7.7	9.9	17.3	21.1	30.4	43.4	57.7	62.4	65.9	74.2	116.7
Avg. Power kW	0.78	0.61	0.35	0.28	0.20	0.14	0.10	0.09	0.09	0.08	0.05

Calculate Attenuation = $(0.424232) \cdot \sqrt{\text{FMHz}} + (0.000563) \cdot \text{FMHz}$ (interactive calculator available at <http://www.timesmicrowave.com>)
 Attenuation: VSWR=1.0; Ambient = +25°C (77°F) Power: VSWR=1.0; Ambient = +25°C (77°F) Conductor = 100°C (212°F);
 Sea Level; dry air; atmospheric pressure; no solar loading



Connectors

Interface	Description	Part Number	Stock Code	VSWR**	Coupling	Inner Contact Attach	Outer Contact Attach	Finish*	Length In (mm)	Width In (mm)	Weight lbs (g)
N/male	Straight Plug	TC-195-NM	3190-1555	<1.25 (2.5)	Knif	Solder	Crimp	SG	1.5 (38.1)	0.75 (19.1)	0.073 (33.1)
SM/male	Straight Plug	TC-195-SM	3190-1553	<1.25 (2.5)	Hex	Solder	Crimp	SSG	1.0 (25.4)	0.32 (8.1)	0.015 (6.8)
TM/male	Straight Plug	TC-195-TM	3190-1554	<1.25 (2.5)	Knif	Solder	Crimp	SG	1.4 (35.6)	0.59 (15.0)	0.046 (20.4)

* Finish metals: N=Nickel, S=Silver, G=Gold, SS=Stainless Steel, A=Aluminum **VSWR spec based on 3 foot cable with a connector pair



Install Tools



Type	Part Number	Stock Code	Description
Crimp Tool	CT-240/200/195/100	3190-687	Crimp tool for LMR 195 connectors
Cutting Tool	CCT-01	3190-1544	Cable end flush cut tool
Replacement Blade	RB-01	3190-1609	Replacement blade for cutting tool